

Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

· 1.1 Product identifier

· Trade name: Nullifire PM015 B

· MSDS code: W-N-PM015B

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture

Epoxy coating Primer / Subcoating

· 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

tremco illbruck Ltd

Coupland Road, Hindley Green, WIGAN, WN2 4HT

Tel: +44 (0) 1942251400, Fax: +44 (0) 1942251410

msds@tremco-illbruck.com

· Further information obtainable from:

tremco illbruck Ltd

Torrington Avenue, Coventry, CV4 9TJ

T: +44 (0) 2476855000, F: +44 (0) 2476469547

www.nullifire.com, protect@nullifire.com

· 1.4 Emergency telephone number:

During office hours tel.: +44 (0) 2476855000. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

· 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02 GHS07 GHS08

- · Signal word Danger
- · Contains:

Benzyl alcohol

(Contd. on page 2)



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

(Contd. of page 1)

cristobalite, crystalline

2,4,6-tris(dimethylaminomethyl)phenol xylene (mix)

· Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H372 Causes damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses, if present and easy to do. Continue rinsing.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous components:		
CAS: 14464-46-1	cristobalite, crystalline	30- <50%
EINECS: 238-455-4	STOT RE 1, H372	
CAS: 100-51-6	Benzyl alcohol	5- <10%
EINECS: 202-859-9 Reg.nr.: 01-2119492630-38-xxxx	Acute Tox. 4, H302; Acute Tox. 4, H332; Eye Irrit. 2,	
		<i>E</i> 400/
CAS: 1330-20-7 EINECS: 215-535-7	xylene (mix)	5- <10%
Reg.nr.: 01-2119488216-32-xxxx	Flam. Liq. 3, H226; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
905-562-9 Reg.nr.: 01-2119555267-33-xxxx	Reaction mass of ethylbenzene and m-xylene and p-	1- <5%
Reg.III 01-2119353267-33-XXXX	Flam. Lig. 3, H226; STOT RE 2, H373; Asp. Tox. 1,	
	H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin	
	Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 67-63-0	propan-2-ol	1- <5%
EINECS: 200-661-7	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3,	
Reg.nr.: 01-2119457558-25-xxxx	H336	

(Contd. on page 3)



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

	(Co	ntd. of page 2)
CAS: 68002-19-7	urea formaldehyde, butylated	1- <5%
	Aquatic Chronic 4, H413]
CAS: 100-41-4	ethylbenzene	1- <5%
EINECS: 202-849-4	Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1,	1
Reg.nr.: 01-2119489370-35-xxxx	H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit.	
	2, H319	
CAS: 90-72-2	2,4,6-tris(dimethylaminomethyl)phenol	1- <5%
EINECS: 202-013-9	Skin Corr. 1B, H314; Skin Sens. 1, H317; Aquatic]
Reg.nr.: 01-2119560597-27-xxxx	Chronic 3, H412	
918-668-5	Hydrocarbons, C9, aromatic	1- <5%
Reg.nr.: 01-2119455851-35-xxxx	Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic]
	2, H411; STOT SE 3, H335-H336	
CAS: 112-24-3	triethylenetetramine	0.1- <1%
EINECS: 203-950-6	Skin Corr. 1B, H314; Acute Tox. 4, H302; Acute Tox. 4,]
	H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out of danger area and lay down.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed

Allergic reactions

Irritating to eyes and skin.

May cause damage to organs through prolonged or repeated exposure.

Harmful if inhaled.

Headache

Dizziness

Nausea

- · Information for doctor: No further relevant information available.
- · Hazards No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

(Contd. on page 4)



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

(Contd. of page 3)

· For safety reasons unsuitable extinguishing agents: Water with full jet

• 5.2 Special hazards arising from the substance or mixture

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Carbon dioxide

- · 5.3 Advice for firefighters
- · Protective equipment: Wear self-contained respiratory protective device.
- Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective clothing.

Keep away from ignition sources.

Ensure adequate ventilation

· 6.2 Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Inform respective authorities in case of seepage into water course or sewage system.

\cdot 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

The usual precautionary measures are to be adhered to when handling chemicals.

Avoid contact with the eyes and skin.

Do not breathe vapour.

Do not eat, drink, smoke or sniff while working.

· Information about fire - and explosion protection:

Flammable liquid and vapour.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Fumes can combine with air to form an explosive mixture.

· 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store only in unopened original receptacles.

· Information about storage in one common storage facility:

Protect from heat and direct sunlight.

Store away from foodstuffs.

· Further information about storage conditions:

Store in cool, dry conditions in well sealed receptacles.

Store receptacle in a well ventilated area.

(Contd. on page 5)



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

(Contd. of page 4)

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with	limit values t	that require mo	onitoring at the	e workplace:
--------------------	----------------	-----------------	------------------	--------------

1330-20-7 xylene (mix)

WEL Short-term value: 441 mg/m³, 100 ppm

Long-term value: 220 mg/m³, 50 ppm

Sk; BMGV

67-63-0 propan-2-ol

WEL Short-term value: 1250 mg/m³, 500 ppm

Long-term value: 999 mg/m³, 400 ppm

100-41-4 ethylbenzene

WEL Short-term value: 552 mg/m³, 125 ppm

Long-term value: 441 mg/m³, 100 ppm

Sk

· Ingredients with biological limit values:

1330-20-7 xylene (mix)

BMGV 650 mmol/mol creatinine

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

· Additional information:

The lists valid during the making were used as basis.

EH40/2005 Workplace Exposure Limits (2nd edition, 2011)

· 8.2 Exposure controls

Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Do not eat, drink, smoke or sniff while working.

· Respiratory protection:

Use only in well-ventilated areas.

Use suitable respiratory protective device when high concentrations are present.

Filter A1/P3

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

(Contd. on page 6)



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

(Contd. of page 5)

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Viscous

Colour: Not determined.

Odour: Solvent-like

Boiling point/Boiling range: > 35 °C

· Flash point: 24 °C

• **Danger of explosion:** Product does not present an explosion hazard.

· Explosion limits:

Lower: Not determined. **Upper:** Not determined.

Vapour pressure: Not determined.

• **Density at 20 °C:** 1.75 g/cm³

· Solubility in / Miscibility with

water: Insoluble.

· Solvent content:

VOC (EU) 210 g/l

• **9.2 Other information** No further relevant information available.

SECTION 10: Stability and reactivity

- · 10.1 Reactivity Stable
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

· 10.3 Possibility of hazardous reactions Reacts with strong oxidising agents.

(Contd. on page 7)



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

(Contd. of page 6)

· 10.4 Conditions to avoid

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Nitrogen oxides

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful if inhaled.

· LD/LC50 values relevant for classification:		
1330-20-7 xylene (mix)		
Oral	LD50	>2000 mg/kg (rat)
Dermal	LD50	3200 mg/kg (rabbit)
Inhalative	LC50/4 h	20 mg/L (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

· Serious eye damage/irritation

Causes serious eye irritation.

· Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Additional toxicological information: Irritating to respiratory system.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure

Causes damage to organs through prolonged or repeated exposure.

· Aspiration hazard Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· 12.1 Toxicity

· /	۱qua	atic	tox	ICI	ty:

1330-20-7 xylene (mix)

LC50/96 h 21.0 mg/L (pimephales promelas)

13.5 mg/L (lepomis macrochirus)

EC50/24 h 165 mg/L (daphnia magna)

- 12.2 Persistence and degradability The product is not easily, but potentially biodegradable.
- 12.3 Bioaccumulative potential May be accumulated in organism
- 12.4 Mobility in soil No further relevant information available.

(Contd. on page 8)



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

(Contd. of page 7)

· Ecotoxical effects:

1330-20-7 xylene (mix)

IC50/72 h 3-5 mg/L (selenstrum capricornutum)

- · Additional ecological information:
- · General notes:

The product contains materials that are harmful to the environment.

Do not allow product to reach ground water, water course or sewage system, even in small quantities.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

Cured product can be deposited together with domestic waste. Observe the specific related regulations of local authorities.

· Waste disposal key: UK (WM3): HP3 HP4 HP5

· European waste catalogue		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
15 01 10*	packaging containing residues of or contaminated by hazardous substances	

- · Uncleaned packaging:
- · Recommendation:

Dispose of packaging according to regulations on the disposal of packagings.

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Non contaminated packagings may be recycled.

SECTION 14: Transport information

· 14.1 UN-Number		
· ADR, IMDG, IATA	UN1263	
· 14.2 UN proper shipping name		
· ADR	1263 PAINT	
· IMDG	PAINT	
· IATA	Paint	
		/Camtal am man

(Contd. on page 9)



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

	(Contd. of page 8)
· 14.3 Transport hazard class(es)	(Conta. or page o)
· ADR	
· Class · Label	3 (F1) Flammable liquids.
· IMDG, IATA	
· Class · Label	3 Flammable liquids. 3
· 14.4 Packing group · ADR, IMDG, IATA	III
· 14.5 Environmental hazards:· Marine pollutant:	No
 14.6 Special precautions for user Danger code (Kemler): 	Warning: Flammable liquids.
EMS Number:	F-E, <u>S-E</u>
· Stowage Category	A
 14.7 Transport in bulk according to Annex Marpol and the IBC Code 	Not applicable.
· Transport/Additional information:	
ADRLimited quantities (LQ)Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
Transport category Tunnel restriction code	3 D/E
· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN 1263 PAINT, 3, III



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

(Contd. of page 9)

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

"CHIP" SI 2009 No.716.

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments). COMMISSION REGULATION (EU) 2015/830 of 28 May 2015

- · National regulations:
- · Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

- · Other regulations, limitations and prohibitive regulations
- · Substances of very high concern (SVHC) according to REACH, Article 57 Not applicable.
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eve irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

SVHC: Substances of Very High Concern

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 11)



Printing date 17.03.2016 Version number 2 Revision: 17.03.2016

Trade name: Nullifire PM015 B

(Contd. of page 10)

Flam. Liq. 2: Flammable liquids, Hazard Category 2 Flam. Liq. 3: Flammable liquids, Hazard Category 3 Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Corr. 1B: Skin corrosion/irritation, Hazard Category 1B Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2: Serious eye damage/eye irritation, Hazard Category 2

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3
STOT RE 1: Specific target organ toxicity - Repeated exposure, Hazard Category 1
STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3 Aquatic Chronic 4: Hazardous to the aquatic environment - Chronic Hazard, Category 4

· * Data compared to the previous version altered.

GB ·