



## Submittal Data Sheet

5 Port Heat Pump, Ductless ODU 4 Ton

5MXS48WVJU9

### FEATURES

- High-efficiency inverter driven swing compressor

### BENEFITS

- 12 Year limited parts warranty with online registration





## Submittal Data Sheet

5 Port Heat Pump, Ductless ODU 4 Ton  
5MXS48WVJU9

EFFICIENCY					PERFORMANCE			
SEER	EER	HSPF	COP		COOLING:		HEATING:	
Non-Ducted:					Rated (Btu/hr):		Rated (Btu/hr):	
Ducted:					Operating Range: 14°F - 115°F		Operating Range: 5°F - 60°F	
Mixed:	0	0	0	0	Rated Cooling Conditions:		Rated Heating Conditions:	
					Indoor (°F DB/DB): 80 / 67 Ambient (°F DB/WB): 95 / 75		Indoor (°F DB/WB): 70 / 60 Ambient (°F DB/WB): 47 / 43	

ELECTRICAL			PIPING			
Power Supply (V/Hz/Ph): *See Engineering Manuals for other voltages.	*208-230 / 60 / 1		Max. System Piping Length: (feet):	268	Gas Conn. (inch):	3/8
System MCA: (Min.circuit amps)	30.8		Max. Interunit Piping Length: (feet):	New Attribute	Liquid Conn. (inch):	1/4
System MFA: (Max.fuse amps)	35.0		Max. Height Difference IDU to ODU (feet):	49.25	Drain Conn. (inch):	
Compressor RLA: (Rated load amps)	27.0		Max. Height Difference IDU to IDU (feet):	98		
Outdoor fan motor FLA: (Full load amps)	0.8		Refrigerant Pre-Charged Pipe Length (ft):	131.2		
Outdoor fan motor W: (Rated output watts)	FanMotorOutput?					

SPECIFICATIONS					
Compressor Type:	Swing		Compressor Stage:	Inverter	
Refrigerant Type:			Refrigerant Oil:	PVE (FVC50K)	
Factory Charge (Lbs):	8.60		Additional Refrigerant Charge (Ozs/ft):	0.21	
COOLING - Airflow Rate (cfm):			HEATING - Airflow Rate (cfm):		
High:	3,684		High:	3,356	
Med:			Med:		
Low:			Low:		
Sound Level (dBA):	53		Sound Level (dBA):	55	
Dimensions (HxWxD) (in):	34-1/4 x 43-5/16 x 18-1/8		Net Weight (lb):	216	





**Submittal Data Sheet**

5 Port Heat Pump, Ductless ODU 4 Ton  
5MXS48WVJU9

**OPTIONAL ACCESSORIES**

<b>INCLUDED</b>	<b>PART NUMBER</b>	<b>DESCRIPTION</b>
No Accessories specified.		