



# Ceiling Cassette

Ceiling Cassette Indoor Unit			CH-09MSPHCT-230VI	CH-12MSPHCT-230VI	CH-18MSPHCT-230VI	CH-24MSPHCT-230VI
Cooling Capacity	BTU/h		9,000	12,000	18,000	24,000
Power supply	V,Hz,Ph		208-230,60,1	208-230,60,1	208-230,60,1	208-230,60,1
Minmum circuit ampacity	A		1,2	1,3	1,9	10,3
Max.fuse	A		15	15	15	17,5
Indoor air flow (Hi/Med/Lo) (No duct)	CFM		353/306/271	338/288/248	562/485/439	820/740/590
Indoor noise level (Hi/Med/Lo) (Standard pressure)	dB(A)		41/39/37	41/38/35	46/43/41	51/47/43
Indoor unit	Dimension (WxDxH)(body)	inch	22.44x22.44x10.24	22.44x22.44x10.24	22.44x22.44x10.24	33.07x33.07x8.07
	Packing (WxDxH)(body)	inch	25.79x25.79x11.42	25.79x25.79x11.42	25.79x25.79x11.42	35.43x35.43x8.86
	Dimension (WxDxH)(panel)	inch	25.47x25.47x1.97	25.47x25.47x1.97	25.47x25.47x1.97	37.4x37.4x2.17
	Packing (WxDxH)(panel)	inch	28.15x28.15x4.84	28.15x28.15x4.84	28.15x28.15x4.84	40.75x40.75x3.54
	Net/Gross weight(body)	lb	35.27/41.88	35.27/41.88	39.68/46.3	45.19/52.91
	Net/Gross weight(panel)	lb	5.51/9.92	5.51/9.92	5.51/9.92	11.02/17.64
Refrigerant piping	Liquid side/ Gas side	inch	1/4"/3/8"	1/4"/1/2"	1/4"/1/2"	3/8"/5/8"
Controller			Remote/Wired control	Remote/Wired control	Remote/Wired control	Remote/Wired control
Cooling	°F		62~90	62~90	62~90	62~90
Heating	°F		32~86	32~86	32~86	32~86
Operation temperature	°F		62~86	62~86	62~86	62~86
Qty/per 20' /40' /40'HQ			234/488/566	234/488/566	234/488/566	148/312/342