

| Floor/Ceiling Indoor Unit | | | CH-18MSPHFC-230VI | CH-24MSPHFC-230VI |
|--|-------------------------|------|----------------------|----------------------|
| Cooling Capacity | BTU/h | | 18,000 | 24,000 |
| Power supply | V,Hz,Ph | | 208-230,60,1 | 208-230,60,1 |
| Minmum circuit ampacity | A | | 1.9 | 2.5 |
| Max.fuse | A | | 15 | 15 |
| Indoor air flow (Hi/Med/Lo) (No duct) | CFM | | 666/595/525 | 880/770/650 |
| Indoor noise level (Hi/Med/Lo) (Standard pressure) | dB(A) | | 47/44/39 | 58.5/55/52 |
| Indoor unit | Dimension (WxDxH)(body) | inch | 42.05x26.57x9.25 | 42.05x26.57x9.25 |
| | Packing (WxDxH)(body) | inch | 45.08x29.72x12.32 | 45.08x29.72x12.32 |
| | Net/Gross weight(body) | lb | 55.12/65.48 | 55.12/66.14 |
| Refrigerant piping | Liquid side/ Gas side | inch | 1/4"/1/2" | 3/8"/5/8" |
| Controller | | | Remote/Wired control | Remote/Wired control |
| Cooling | °F | | 62~90 | 62~90 |
| Heating | °F | | 32~86 | 32~86 |
| Operation temperature | °F | | 62~86 | 62~86 |
| Qty per 20' /40' /40'HQ | | | 102/220/252 | 102/220/252 |

Universal Floor/Ceiling

