

CORE RANGE

FIRECHIEF®
making the world a safer place

FIRECHIEF CTX SPRAY FOAM EXTINGUISHERS

MODEL:

CXF6 **CTX**
CXF9

- Kitemark certified to BS EN 3
- 5 year guarantee
- Both sizes carry 75F fire rating
- 35kV dielectric test
- Squeeze grip operation
- Internal polyethylene lining
- Spray Nozzle
- Corrosion resistant finish



CXF9
100-1611

CXF6
100-1610



+44 (0) 330 999 0019

sales@firechiefglobal.com

firechiefglobal.com

FIRECHIEF CTX SPRAY FOAM EXTINGUISHERS



The Firechief CTX Foam Extinguishers are an excellent solution for multi-risk usage. Ideal for use on A class fires (wood/paper), B class (petrol & volatile liquids), and F class (cooking oil), the foam forms a flame smothering seal to prevent reignition.

MODEL:

CXF6 **CTX**
CXF9



Specifications

Model	CXF6	CXF9
Product Code	100-1610	100-1611
Description	Firechief CTX 6L Foam Extinguisher	Firechief CTX 9L Foam Extinguisher
Capacity (l)	6	9
Fire Rating	21A 144B 75F	21A 183B 75F
Discharge Time (secs)	≥15s	≥15s
Working Pressure (bar)	12	12
Temperature Range (°C)	+5 to +60	+5 to +60
Product Height (mm)	535	600
Product Diameter (mm)	162	184
Filled Weight (kg)*	9.3	13.7
Carton Height (mm)	570	620
Carton Length (mm)	175	195
Carton Width (mm)	170	190
Packaged Weight (kg)**	10	14.5
Product EAN	5055377962821	5055377962838

* Extinguisher, contents and plastic base only (where applicable) - not including hose, bracket or packaging.

** Includes all packaging, hose / horn and bracket.

For more information contact: Firechief Global, 3 Lands End Way, Oakham, Rutland, UK, LE15 6RB | Imported into EU by: Firechief Global (EU) Ltd, 3rd Floor, 40 Mespil Rd, Dublin 4, Ireland, D04 C2N4



+44 (0) 330 999 0019



sales@firechiefglobal.com



firechiefglobal.com