

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

No. FB760 – 20160308

- 1. Unique identification code of the product-type:** FB760
- 2. Intended use/es:** A compressible combination of reactive and non-reactive components, encased in a thin woven glass fibre casing used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.
- 3. Manufacturer:** tremco illbruck Limited, Coupland Road, Hindley Green, Wigan, UK. WN2 4HT
- 5. System/s of AVCP:** System 1
- 6. European Assessment Document:** ETAG 026 edition 2011 used as EAD  
**European Technical Assessment:** ETA 14/0055 of 19/02/2014  
**Technical Assessment Body:** Warrington Certification Limited  
**Notified Body:** 1121, Warrington Certification Limited
- 7. Declared performance/s:**

Essential Characteristic	Performance	Harmonised Technical Specification
<b>Safety in Case of Fire</b>		
Reaction to fire	Class F	EN13501-1
Resistance to fire	Up to EI120 Resistance to fire performance, in accordance with EN13501-2 See ETA 14/0055 - Annex C	EN13501-2 EN1366-3: 2009
<b>Hygiene, Health and Environment</b>		
Dangerous Substances	Does not contain dangerous substances See ETA 14/0055 Clause 3.5	
Air Permeability	Test Pressure Differential 600 Pa See ETA 14/0055 Clause 3.3	EN 1314-1
<b>Energy, Economy and Heat Retention</b>		
Service & Durability	Z <sub>1</sub> intended for use in internal conditions with humidity ≥85% RH, temperatures ≥ 0° C, without exposure to rain or UV in accordance with EOTA Technical Report TR024 – Edition November 2006	ETAG 026-3

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

**Signed for and on behalf of the manufacturer by:**  
M. Liptrot, Business Unit Director Sealants & Coatings  
At Wigan on 8<sup>th</sup> March 2016



**Annex:**

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is available on the website to support this Declaration of Performance.

# DECLARATION OF PERFORMANCE

According to ANNEX III of the regulation (EU) N° 305/2011

**Nullifire**  
Smart Protection

No. FB760 – 20160308

<b>CE</b>	
tremco illbruck Limited, Coupland Road, Hindley Green, Wigan. WN2 4HT UK 14 1121-CPR-JA5012 FB760 – 20160308 www.nullifire.com/FB760/	
EN 1366-3: 2009 ETA 14-0055 ETAG 26, Part 3	
A compressible combination of reactive and non-reactive components, encased in a thin woven glass fibre casing used to reinstate the fire resistance performance of wall constructions where they have been provided with apertures for the penetration of single or multiple services.	
Essential Characteristic	Performance
Safety in Case of Fire	
Reaction to fire	Class F
Resistance to fire	Up to EI120 Resistance to fire performance, in accordance with EN13501-2 See ETA 14/0055 - Annex C
Hygiene, Health and Environment	
Dangerous Substances	Does not contain dangerous substances See ETA 14/0055 Clause 3.5
Air Permeability	Test Pressure Differential 600 Pa See ETA 14/0055 Clause 3.3
Energy, Economy and Heat Retention	
Service & Durability	Z <sub>1</sub> intended for use in internal conditions with humidity ≥85% RH, temperatures ≥ 0° C, without exposure to rain or UV in accordance with EOTA Technical Report TR024 – Edition November 2006
Other	NPD